

SPECIFICATIONS (UT58A)

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2V/20V/200V/1000V	± (0.5%+1)
AC Voltage	2V/20V/200V/750V	± (0.8%+3)
DC Current	20µA/2mA/20mA/200mA/20A	± (0.8%+1)
AC Current	2mA/200mA/20A	± (1%+3)
Resistance	200Ω/2kΩ/20kΩ/2MΩ/20MΩ/200ΩM	± (0.8%+1)
Capacitance	2nF/200nF/100µF	± (4%+3)
Special Functions		
Diode		✓
Continuity Buzzer		✓
Transistor		✓
Data Hold		✓
Full Icon Display		✓
Sleep Mode		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Max Display	1999	✓

GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	60 x 54mm
Product Colour	Grey Holster - Red
Product Net Weight	350g (including holster)
Product Size	179 x 88 x 39mm
Standard Accessories	Test Lead, Battery, English Manual, Multi-Purpose Socket, Holster
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	40pcs
Standard Carton Measurement	598 x 418 x 340mm (0.085 CBM Per Standard Carton)
Standard Carton Gross Weight	27kg

Specifications and other information are subject to change without further notice.

[Back to main menu](#)